



US008474144B2

(12) **United States Patent**
Royle

(10) **Patent No.:** **US 8,474,144 B2**
(45) **Date of Patent:** ***Jul. 2, 2013**

(54) **SAFETY RAZOR WITH ROTATIONAL
MOVEMENT AND LOCKING BUTTON**

(75) Inventor: **Terence Gordon Royle**, Basingstoke
(GB)

(73) Assignee: **The Gillette Company**, Boston, MA
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 353 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **12/752,200**

(22) Filed: **Apr. 1, 2010**

(65) **Prior Publication Data**

US 2011/0035950 A1 Feb. 17, 2011

Related U.S. Application Data

(60) Provisional application No. 61/233,159, filed on Aug.
12, 2009.

(51) **Int. Cl.**
B26B 21/52 (2006.01)

(52) **U.S. Cl.**
USPC **30/532; 30/527**

(58) **Field of Classification Search**
USPC 30/32, 33, 37, 58, 61, 67, 66, 87,
30/526, 527, 528, 529, 47, 51, 57, 530-533
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,211,255 A * 8/1940 Claassen 30/532
3,950,848 A 4/1976 Goldstein
3,964,160 A 6/1976 Gordon

4,083,103 A * 4/1978 Estandian 30/47
4,275,498 A 6/1981 Ciaffone 30/47
4,347,663 A * 9/1982 Ullmo 30/47
4,475,286 A * 10/1984 Saito 30/527
4,573,266 A * 3/1986 Jacobson 30/41
4,797,998 A 1/1989 Motta
4,922,609 A * 5/1990 Grange 30/57

(Continued)

FOREIGN PATENT DOCUMENTS

DE 202006011254 U1 1/2007
WO WO-2011/094887 A1 8/2011

(Continued)

OTHER PUBLICATIONS

PCT International Search Report with Written Opinion in corre-
sponding Int'l appln. PCT/US2010/044519 dated Oct. 20, 2010.

Primary Examiner — Kenneth E. Peterson

Assistant Examiner — Fernando Ayala

(74) *Attorney, Agent, or Firm* — Joanne N. Pappas; Kevin C.
Johnson; Steven W. Miller

(57) **ABSTRACT**

A safety razor including a handle having a grip portion and a
connection portion secured to the grip portion. The connec-
tion portion rotates with respect to the grip portion about a
rotational axis. A blade unit is mounted to the connection
portion by a connection member. The handle includes an
ejector button having a first position locking the connection
portion with respect to the grip portion preventing the con-
nection portion from rotating with respect to the grip portion,
a second position allowing the connection portion to rotate
with respect to the grip portion, and a third position for
ejecting the blade unit from the connection portion.

17 Claims, 9 Drawing Sheets

